

IN THE CLAIMS

Please amend claims 4-8, 14, 15, 17, 21-28, and 30 as follows.

cl  
am 4  
4. Apparatus according to Claim 3, characterised in that the tongues (23) are circumferentially distributed in several sets of tongues (23) each including at least one tongue.

a1  
Sub  
B17  
5. Apparatus according to Claim 4, characterised in that the tongues (23) extend radially above the second surface (2).

6. Apparatus according to Claim 4, characterised in that the tongues (23) extend opposite the second surface (2).

cl  
am 4  
7. Apparatus according to Claim 6, characterised in that the casing (30) has casing elements (7, 8-3, 6) each provided at their external periphery with an axially oriented annular flange (7, 6) and in that the tongues (28) are connected to one of the flanges (6, 7).

8. Apparatus according to Claim 5, characterised in that the tongues (23) are fixed to the piston (4) and to the transverse wall (3).

a2  
cl  
am 4  
14. Apparatus according to Claim 13, characterised in that the second piece (25) is distinct from the flange (6, 7) and has transverse lugs (53) provided in the free end of the relevant flange (6, 7).

a2  
cont  
C1  
cont  
15. Apparatus according to Claim 14, characterised in that the lugs (53, 44) on the second (25) and first (24) pieces are fixed respectively to the flange (6, 7) and to the skirt (27) of the piston.

a3  
C1  
cont  
17. Apparatus according to Claim 16, characterised in that the second piece has the shape of an angle bracket and has a transversely oriented part to which the tongues (23) are fixed and an axially oriented part having the transverse lugs (53) at its external periphery.

C1  
cont  
a4  
19. Apparatus according to Claim 20, characterised in that the tongues are fixed by riveting.

22. Apparatus according to Claim 21, characterised in that the hub (14) has an axially oriented annular part (16) directed towards the transverse wall and in that the piston (4) surrounds the said axially oriented annular part (16) of the hub (14) with an annular clearance.

23. Apparatus according to Claim 22, characterised in that the <sup>a</sup> <sup>47</sup> torsion damper (28) is interposed between the piston (4) and the transverse wall (3) in order to filter the vibrations, the said damper acting disengageably between the piston (4) and the hub (14).

24. Apparatus according to Claim 23, characterised in that the torsion damper has two guide washers (36, 37) disposed on each side of the damper plate (35) connected with respect to rotation,

possibly with take up of clearance, with the hub (14), in that a disc (31) is fixed to the guide washers (36, 37) and in that the disc (31) is intended to be clamped between the first and second surface (1,

2).

CI  
cont

25. Apparatus according to Claim 24, characterised in that the disc (31) carries on each of its faces a friction lining (33) and in that the linings (33) are intended to be clamped between the surfaces (1, 2).  
49

ay

26. Apparatus according to Claim 25, characterised in that the disc (31) is fixed to flanges pressed against each other (55, 155) which the guide washers (36, 37) have at their external periphery.  
ries

27. Apparatus according to Claim 26, characterised in that the hub (14) has an axially oriented annular part (16) with a surface (20) surrounded by a ferrule (22) which the piston has at its internal periphery and in that the surface (20) is extended in the direction of the transverse wall by flutes (19) for a rotational connection, possibly with the taking up of a circumferential clearance, of a hub (35) on the torsion damper (28).  
38  
Col 2, line 6, spined  
the damper plate

28. Apparatus according to Claim 27, characterised in that a friction means (60) acts between a transverse surface (15) of the hub (14) and the piston (4) and in that the piston (4) is shaped so as to carry the friction means (60), and in that the hub (14) has ~~an~~ <sup>the</sup> axially oriented annular portion (16) directed towards the transverse wall (3) and surrounded by the piston (4) mounted so as to be able to move axially with respect to the said portion.

ay  
cl  
cont

30. Apparatus according to Claim 29, characterised in that the turbine wheel (12) has an annulus (13), possibly divided, <sup>?</sup> fixed to the hub (14) by means of a rivet (59), in that a friction means (60) acts between the hub (14) and the piston (4) and in that the friction means (60) is carried by at least

fig 46-58

at  
cont  
As

one rivet (59).

TO 9220 " SEC 090860